




HYDRAULIC WINCH



- Oil immersed negative brake for low running costs.
- Double line pull winch for an ideal compromise between pulling effort & speed (except winch 3t TD- direct hook mount).
- Standard cable guide for easy operations.
- Storage stand preventing any contact between the winch & the ground, as well as ensuring a permanent cable tension.





End of cable/ hook upper position automatic movement stop



Safety: homologated self locking swivel hook

* Hook speed without load
** without stand

	Winch 3T	Winch 3T MRT 3255	Winch 3T TD	Winch 4T	Winch 5T	Winch 7.2T
Hook Capacity (kg)	3000	3000	3000	4000	5000	7200
Forward reach / depth (mm)	763	763	839	838	838	638
Cable length (m)	49	70	48	51	51	76
Working height (m)	24	33	46	24	24	36
Speed (m/min) *	24	24	48	21.5	21.5	19.4
Cable loops	1	1	Direct	1	1	1
Weight (kg) **	395	395	480	510	510	700

Machine compatibility

Reference	885236	N/A	N/A	N/A	N/A	N/A
MT 835	x					
MT 1135	x					
MT 1335	x					
MT 1440	x					
MT 1840	x					
Reference	885236		N/A	711933		
MRT-X Easy	x			x		
E-RECO	921337	939393	939111	921338	921341	934500
MRT Easy €3B	x			x		
MRT 2145 Easy €3B	x		x	x		
MRT Privilege +	x			x	x	
MRT 3255		x	x		ref.939109	x

MANDATORY MACHINE EQUIPMENT: 