


PB S320 Series

Self-propelled Scissor lifts

Working height 32.14 m / 1,40 m - 1,80m - 2,40 m width

4-wheel-drive + 2-axles-steering / Automatic supports system



Type	PB S320-14ES 4x4	PB S320-18ES 4x4	PB S320-24ES 4x4*
Operation area	indoor	in-/+outdoor	in-/+outdoor
Drive	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Alternative Drive	-	-	Diesel-hydraulic (PB S320-24DS 4x4)
Working height	31,87 m	32,14 m	31,80 m
Platform height – raised	29,87 m	30,14 m	29,80 m
Drivable at full height	Yes	Yes	Yes
Platform size (lxw)	6,15 m x 1,20 m	6,15 m x 1,80 m	6,15 m x 2,40 m
Platform size max. (lxw)	7,65 m x 1,20 m	8,40 m x 1,80 m	8,40 m x 2,40 m
Lift capacity	750 kg	750 kg	750 kg
Lift capacity extension	750 kg	750 kg	750 kg
Platform occupancy max.	4	4	4
Total weight	23.790 kg	24.220 kg	≈ 26.500 kg (23.350 kg)
Total length	6,60 m	6,60 m	6,60 m
Total width	1,40 m	1,80 m	2,40 m
Total height	4,22 m	4,25 m	4,25 m
Transport height	3,25 m	3,30 m	3,30 m
Turning radius – outside	8,44 m	6,30 m	6,30 m
Ground clearance – center	0,27 m	0,27 m	0,27 m
Gradeability	25 %	25 %	25 %
4-wheel-drive	Standard	Standard	Standard
2-axles-steering	Standard	Standard	Standard
Differential lock	Standard	Standard	Standard
Autom. Supports system	Standard	Standard	Standard
Engine power	20 kW	38 kW	38 kW (36,3 kW Deutz)
Battery capacity	800 Ah5, 80V	930 Ah5, 80V	930 Ah5, 80V (180 Ah)



* Provisional data. Technical data are subject to change.



Platformers Business

PB Liftechnik GmbH | Gewerbegebiet Gassenäcker | 89429 Oberbechingen / Germany

Telephone: +49 (0) 90 77 – 95 00 – 0 | Telefax: +49 (0) 90 77 – 95 00 – 40

E-Mail: info@PBgmbh.de | Website: www.PBgmbh.de

